



TECHNICAL SPECIFICATIONS

ECCODAL 50

TECHNICAL INFORMATION

SPECIFICATIONS	DOC.	UNIT	VALUE	MIN	MAX
Compressive strength	PTV 828	kN ton/sqm	- -	110 228,3	- -
Deformation (40 kN)	PTV 828	%	-	-	1,8 %
Tensile strength	PTV 828	kN/m	-	1	-
Connection type Connections	PTV 828	- pcs	fix 8	-	-

OTHER SPECIFICATIONS

Composition	PE (polyethylene)
Weight per tile	3 904 g
Length (including connections)	80 cm
Width (including connections)	80 cm
Height	5 cm
Cell thickness	0,35 - 0,40 cm
Colour	green or black





ECCODAL 40

TECHNICAL INFORMATION

SPECIFICATIONS	DOC.	UNIT	VALUE	MIN	MAX
Compressive strength	PTV 828	kN ton/sqm	- -	110 228,3	- -
Deformation (40 kN)	PTV 828	%	-	-	2,1 %
Tensile strenght	PTV 828	kN/m	-	1	-
Type of joint Joints	PTV 828	- pcs	fix 8	-	-

OTHER SPECIFICATIONS

Composition	PE (polyethylene)
Weight per tile	3 172 g
Length (including connections)	80 cm
Width (including connections)	80 cm
Height	4 cm
Cell thickness	0,35 - 0,40 cm
Colour	green or black

ECCOdal is a registered trademark in class 17, 19 and 35.
ECCOdal grass grids are delivered on disposable pallets (81 x 81 cm)

